



NILES EXPANDED METALS & PLASTICS

SECUREX SAFETY RAIL – 42" HIGH PARTIAL FILL PANEL (available in steel or aluminum)

Mesh size options:67"w x 15"h with u-edging 67"w x 16"h with u-edging
Mesh panels per section:2
Number of Rails:3
Fittings (per section):Iron Casting – Kee Safety Fittings meeting ASTM A47-77-32510
Post Height:42"
Maximum Span:72"
Framework Options:Posts: 1-5/8" (1.660 OD) WT/SS40 round framework Posts: 2" (1.900 OD) WT/SS40 round framework
Fasteners:Hardened steel hexagon set screws
Color Options Framework:Hot Dip Galvanized to meet ASTM A123 Powder Coat - Safety Yellow, Black, Green
Expanded Metal Infill:Hot Dip Galvanized to meet ASTM A123 Powder Coat – Safety Yellow, Black, Green
Expanded Metal Infill Style Designations: $\frac{1}{2}$ -#13R $\frac{3}{4}$ -#9R $\frac{3}{4}$ -#9F $1\frac{1}{2}$ -#9R 2-#9R
Accessories Available:Toeboards - OSHA 1910.23 ADA Compliant Handrail Shelving

All Securex systems assume reverse diamond orientation unless otherwise requested.
Mesh panel size and configuration can be adjusted to design requirements.

